



PERFORATED TABLES FOR LAMINAR FLOW



Length	500, 600, 700, 800, 900, 1000, 1100, 1200, 1300, 1400, 1500, 1600, 1700, 1800, 1900, 2000
Depth	600, 700, 800

Frame structure in stainless steel AISI 304 fully welded 40x40mm tube, 1.00mm thick, rear legs 80mm advanced, suitable for rounded floor corner. Rear and side welded reinforcement rails. Perforated working top in AISI 304 s.s. sheet, 1.50mm thick. Hole diameter 9mm and perimetral frame 60mm wide. Rounded (R=10mm) front upper edge, as well as rounded (R=2mm) side and back edges. On adjustable feet.

SKU: N/A



L	W		
	600	700	800
	Cod.	Cod.	Cod.
500	T06001001	T06002001	T06003001
600	T06001002	T06002002	T06003002
700	T06001003	T06002003	T06003003
800	T06001004	T06002004	T06003004
900	T06001005	T06002005	T06003005
1000	T06001006	T06002006	T06003006
1100	T06001007	T06002007	T06003007
1200	T06001008	T06002008	T06003008
1300	T06001009	T06002009	T06003009
1400	T06001010	T06002010	T06003010
1500	T06001011	T06002011	T06003011
1600	T06001012	T06002012	T06003012
1700	T06001013	T06002013	T06003013
1800	T06001014	T06002014	T06003014
1900	T06001015	T06002015	T06003015
2000	T06001016	T06002016	T06003016

W = Width / Profondità / Breite / Profondeur.

L = Length / Larghezza / Länge / Longueur.